Evidence of Performance

Burglar resistance

Test Report

(PB-D02-05-en-02)

N° 17-002022-PR04

Client agtatec ag Allmendstr. 24

> 8320 Fehraltorf Switzerland

Burglar resistant automatic sliding door Product

record THERMCORD RC3 Designation

Overall dimensions 4,205 mm x 2,950 mm $(W \times H)$

(Frame) Aluminium, THERMCORD 38 Material, System

Attack side Outside of building

Slide, scheme C Type of opening

> Double-pane insulating glass, Class P5A as per EN 356 Infill panel

agtatec associated hardware with 3 rollers per sash, continuous guide at bottom, 2 locks per sash,

electromechanical locking device Hardware

According to installation instruction from company agtatec ag Installation

> The control unit must be installed in such a way that a minimum distance of 1,200 mm is ensured between the

outermost element edge and the operating unit. Special features

Burglar resistance



Class RC 3

ift Rosenheim 25.05.2018

Translation dated 02.11.2022

Lalibrier-, Zertin-Herungsstr ift Rosenheim GmbH Theodor-Gietl-Str. 7-9 83026 Rosenheim FH) **** rosenheit Simon Stüer Operating Te Germany

signed Konrad Querengässer, Dipl.-Ing. (FH) Head of Testing Department Security/Safety Testing

Operating Testing Officer Security/Safety Testing

This document is valid without a signature. The original document n° 17-002022-PR04 (PB-D02-05de-02) dated 25.05.2018 remains legally binding.



Basis

DIN EN 1627: 2011 Pedestrian doorsets, windows. curtain walling, grilles and shutters - Burglar resistance -Requirements and classifications

DIN EN 1628 : 2011 DIN EN 1629: 2011 DIN EN 1630: 2011

Replaces Test report n° 17-002022-PR04 (PB-D02-05en-01) dated 27.06.2018

Representation



Instructions for use

This test report serves to demonstrate burglar resistant characteristics

Validity

The data and results given refer solely to the tested and describes specimen. Testing to burglar resistance does not allow any statement to be made on any further characteristics of the present structure regarding performance and quality.

In deviation from the tested type, the following dimensional changes are permitted: Distance A +5% and -20% Distance B +5% and -30% Surface +25%

Notes on publication

The ift Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

The cover sheet can be used as abstract.

Contents

The report contains a total of 56 pages

- Object
- Procedure
- Detailed results Annex 1 (18 pages) Annex 2 (6 pages) Annex 3 (13 pages)



